A boby in a cradle carry in a pouch or ring sling should be positioned a cardle carry in a pouch or ring sling should be positioned carefully with their bottom in the deepest part so the sling does not fold them in half pressing their chin to their chest.

their furmmy and chest are against you, if a sling is too loose they can slump which can partially close their airway. This can be lested by placing a hand on your Close to the wearer so their back is supported in its natural position and



aywoka a sbace ot at Jeast a fluder width under your bapk's chin.

KEEP CHIN OEF THE CHEST – a papk shonld never be curled so their chier is



CTOSE ENONGH 10 KIZS – hont paph's yeard shonly be as close to hont pead forward hon shonly be aple of its cowfortaple. By flibbing your head forward you should be oble



Aont popk atoniq face namaraz vol pe Inuweq iu tomarqa kont. poqk atoniq Ipeus ao kon thore jo obeu ji to atvect ou Ipeus. Ju a caaqle boalijou ha **NEM 21 ATI LIMES** – kon atoniq ajmaka pe opije io see koni papk, a face




preathing and pull on your back. TIGHT – slings and carriers should be tight enough to hug your boby close to you both. Any slack/loose fabric to you as this will be most comfortable for you both. Any slack/loose fabric will allow your boby to slump down in the carrier which can hinder their backling look to the property of the prope



NOPPORTED BACK

★ KEEP CHIN OFF THE CHEST
 ★ C







When you're wearing a sling or carrier, don't forget the **T.I.C.K.S.** Keep your baby close and keep your baby safe.

The T.I.C.K.S. Rule for Safe Babywearing

with a tew easy adjustments. pspywearing group wearing is often fixable take a mirror selfie and post it to an online If you can't find a local babywearing group,

tor the tabric than powdered. the rings too easily. Liquid detergents are better softeners can cause the fabric to slip through sling! Bleach will damage the fibers and fabric Never use bleach or fabric softener on your ring

through the rings, or even just sitting on it! it by steam ironing, running it back and forth If your sling is still new and stiff, you can soften

the rings from banging around in the dryer. sock over the rings before tumble drying to keep To wash your sling, put it inside a pillowcase or laundry bag and wash on cold. Put a clean dry



Everyday Babywearing






Seat-making tips in a ring sling




 Wrapyouinlove (pasics) Mewborn ringsling 'classic'

puils puix ruox puist




1) Start with rings on your shoulder, with the fabric spread across your back. Bring the tail up through the rings, then down over the 1st ring and under the 2nd. Work your thumbs under the fabric over the first ring and use your index fingers to walk the fabric from one hand to the other hand to straighten it out.



Place the rings at "corsage" position* with the fabric capping your shoulder from neck down the top of your arm. There should only be enough slack for baby - no extra.

Use your arm to gauge space.

*If you struggle with the rings ending too low, you can start the rings up high on top of your shoulder.)



4) Find the **top rail*** and pull the it up snugly over baby's back. Newborns need the wrap up to their neck. Older babies (of an age that you would naturally pick them up under their armpits) can have the rail pulled up to their armpit level with their arms out. All extra


fabric should be bunched under baby's knees. Knees should be higher than their bum in an "M" shape. Gently push up on baby's heels to deepen the seat if needed.



5) To tighten the bottom rail or the middle of the sling, lift baby's bum to take the weight off the rings and pull the outside or center of the tail straight down and slightly away from your body.
Baby's knees should be higher than
their burn, but the middle of the wrap should be snug enough that their bum doesn't "sag" down. It should look like a well supported hammock seat.

*The *top rail" is the edge that extends from the inside edge of the rings, around the top of your back, behind baby's neck, and down the inside of the tail nearest to baby.

The *bottom rail" is the edge that goes around the wearer's arm, under baby's knees and to the outside of the tail away from baby.



3) Place baby at desired final placement. Newborns should be centered high on your chest. As they get older they can be moved off center, and sitting babies can be moved all the way over onto your hip.

Take this opportunity move any loose fabric around your back, under baby and toward the rings. Pull the tail down so that the bunched fabric under baby is snugly supporting baby under their knee-pits.



To tighten the top rail, use your hand opposite the ring side to lift baby's weight up and your ring-side hand to pull the top rail **horizontally** behind baby's neck. Pulling straight down can cause the fabric to bunch in the rings. Ideally, the top rail should end up completely horizontal from the rings to your opposite armpit.

If the wearer leans forward, baby should not gap away from the wearer but should still be snug and supported.